

Connector - FL LCX CON-N-F E - 2702518

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The length of the leaky wave conductor must be adapted to the special length in the application. Connectors are then installed at both cable ends. Wireless devices can be connected to these via a flexible connecting cable.



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	160.000 g
Custom tariff number	85366910
Country of origin	Belgium

Technical data

General

Frequency range	2.4 GHz ... 6 GHz
Impedance	50 Ω
Connection method	N (female)
Mounting type	other

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	19070490
eCl@ss 7.0	19070490

Connector - FL LCX CON-N-F E - 2702518

Classifications

eCl@ss

eCl@ss 8.0	19070417
------------	----------

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002635
ETIM 5.0	EC001135

UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601