



RECOMMENDED LAND PATTERN DIMENSION OF PCB
(PCB THICKNESS: t=1.6mm METAL MASK THICKNESS: t=0.12mm)

- NOTE 1 Lead CO-Planarity is 0.1mm MAX.
 2 Floating range of this connector is ±0.6mm MAX.
 3 It shows the vacuum pickup area.
 4 Packing for product applies embossed carrier tape packing. (500pcs/RL)
 5 Blemish and hit mark can be occurred through out the manufacturing process which doesn't affect quality level.
 6 The dimensions in parentheses are for references.

3	COPPER ALLOY	CONTACT AREA: GOLD 0.1 μm	6	POLYESTER	(EMBOSSED COVER TAPE)	
		LEAD AREA: GOLD 0.03 μm		5	POLYSTYRENE	(EMBOSSED CARRIER TAPE)
		UNDER PLATING: NICKEL 1.3 μm		4	BRASS	TIN-PLATING 3 μm
2	POLYAMIDE	BLACK UL94V-0	4	BRASS	UNDER PLATING: NICKEL 1 μm	
1	POLYAMIDE	BLACK UL94V-0				
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS	
UNITS mm		SCALE 2 : 1	COUNT	DESCRIPTION OF REVISIONS		
APPROVED : HS. OKAWA		14.06.26	DRAWING NO. EDC3-352599-00			
CHECKED : KN. SHIBUYA		14.06.26	PART NO. FX22-80P-0.5SH			
DESIGNED : AH. EDASHIGE		14.06.26	CODE NO. CL572-3004-2-00			
DRAWN : AH. EDASHIGE		14.06.26	DATE			

4 DRAWING FOR PACKING

